

EPPS93-M

60kW 93kWh Liquid Cooling Mobile Power Unit
For Comprehensive Off-grid Power Supply



All-in-One

- Highly integrated battery inverter, ESS, fast charge input, EV charger, liquid cooling, optional solar inverter system in a compact cabinet
- Multiple usage scenarios



High Performance

- High quality LFP cells
- Up to 60kW DC charge output
- Broad temperature range for use



Robustly Designed

- 8mm steel galvanized cold rolled coil chassis
- 4mm 360° full body protection
- Automotive-grade waterproof components



Off-grid AC Output

- Energy independent for household
- Up to 33kVA AC output for use
- Single and three phase sockets availability

EPPS93-M

60kW 93kWh Liquid Cooling Mobile Power Unit

AC Input Parameters		
Rated Voltage	400 Vac, 3W+N+PE	
Nominal Frequency	50 Hz	
Rated Charging Power	30 kW	
Input Socket	CEE Socket 125A	
THD-I	<3%	
* 30 kW refers to the maximum charging power to the battery. When supplying bypass load simultaneously, the actual input power may exceed 30 kW depending on load demand.		
DC Input Parameters		
Nominal Voltage	332.8 V	
Voltage Range	260 Vdc ~ 379.6 Vdc	
Max. Current	168 A	
Max. Power	60 kW	
DC Input Socket	GB/T Socket	CCS2 Socket
PV Input Parameters (Optional)		
Max. Power	30 kW	
MPPT Voltage Range	150 Vdc ~ 425 Vdc	
Max. PV Input Current	84 A	
MPPT Trackers/ Strings	2/4	
PV Input Socket	4 x MC4	
DC Output Parameters		
Product Model	EPPS93-M(GB/T)	EPPS93-M(CCS2)
Max. Output Power	60 kW	60 kW
Output Voltage Range	150 Vdc ~ 1,000 Vdc	150 Vdc ~ 1,000 Vdc
Max. Current	200 A	200 A
Output Plug	GB/T Plug	CCS2 Plug
AC Output Parameters		
Rated Voltage	230 Vac	400 Vac
Max. Output Power	33 kVA	
Max. Output Current	16 A	47 A
Output Socket	2 * Type E	CEE Socket 63A
General Parameters		
Nominal Energy	93 kWh	
Usable Energy	84 kWh	
Cell Type	LFP	
Altitude	<2,000 m, Derating Above 2,000 m	
Operating Relative Humidity	5 ~ 95%RH, No Condensation	
Operating Temperature Range	-20 °C ~ 50 °C, Derating Above 45 °C	
Thermal Management Mode	Liquid Cooling & Heating	
Rated Cooling Input Power	3 kW	
Ingress Protection	IPX4	
Anti Corrosion Grade	C4	
Dimensions (W*D*H)	1,600 mm*1,100 mm*1,580 mm	
Weight	~1,500 kg	

